

CHLORINE GENERATOR INSTRUCTIONS

WITH PUMP ON AND TIMER TABS REMOVED:

- Once the salt is delivered, use your pool brush to stir up any non-dissolved traces of salt.
- Add two 1 pound bags of shock.
- Wait 24 hours.
- Reset Generator by flipping timer switch off then back on – a lot of lights will flash for two to three minutes – that’s normal.
- Look at the *Salt Level* lights on your Generator, if it glows red or yellow, add one 50 pound bag of salt right into your pool (not the skimmer) and let dissolve.
- Wait 12 – 24 hours, reset Generator and look at *Salt level* lights – add salt if necessary.
- When the *Salt Level* light is Green, set the *Sanitizer Output* level to 60% by pressing the MORE or LESS button.
- Wait 24 hours, test the water for Chlorine, the ideal range is 1 – 3 PPM. Adjust as needed by using the MORE or LESS buttons.
- Adjust *Sanitizer Output* (chlorine) level one (20%) increment at a time, and allow 24 hours before testing again.
- Set your timer tabs and resume use as normal.
- Your specific output setting may be much different from your neighbors, it depends on a lot of variables.
- The ideal Salt Reading is from 2900 – 3000 PPM.

TIPS FOR SUCCESSFUL USE:

- Use stabilizer/conditioner to stabilize Chlorine in your pool.
- The Generator does not work or light up if the pump is not on.
- The Generator will not produce Chlorine if the water temperature is below 59 degrees Fahrenheit.
- A lot of lights will flash for several minutes every time the Generator is powered up.
- All of this information is in the User’s Guide that came with your Intellichlor Generator.
- You can “Shock” your pool by pressing both the MORE & LESS buttons at the same time, a lot of lights will flash.
- If any *Status* light does not illuminate, don’t be alarmed, it may take 5 – 50 minutes for it to come on.